



PRIME

DESCRIPTION

PRIME is a water based pigmentable acrylic primer which provides a flat, uniformly absorbent, color coordinated surface for application of FlexCoat Acrylic or Perfector Acrylic finishes. PRIME is recommended for the surface preparation of Polybase Wet/Dry/NC, GreatWall, interior drywall, concrete, masonry and stucco to color coordinate the substrate with the finish. PRIME enhances color consistency, reduces flashing, increases texture consistency, improves bond strength and coverage, and increases working time in hot, dry weather.

ADVANTAGES

- Improves color consistency across the wall
- Prevents flashing
- Improves finish coverage in certain situations

PACKAGING

60lb (27kg) pail.

COVERAGE

Approximately 800ft² (74m²)* per 60lb (27kg) pail, depending upon surface roughness and porosity of the substrate.

*Coverage given is approximate and will vary depending on substrate, details and individual application technique.

PREPARATION

Surfaces shall not be below 4°C (39°F) and must be clean, dry, structurally sound, and free of efflorescence, grease, oil, form release agents, curing compounds and any other deleterious materials.

MIXING

Add 1 bottle of Liquid Colorant for desired shade and stir to a smooth, homogeneous consistency. Addition of color is optional, but recommended especially for deep tint scroll finishes.

DRYING

The drying time of PRIME is dependent upon the air temperature and relative humidity. Under average weather conditions, 15C (59°F) 55% RH, PRIME is dry to the touch in ½ hour and sufficiently dry for application of finish in 2 hours. Protect from rain for at least 4 hours.

CLEAN-UP

Clean tools with water before PRIME dries.

STORAGE

Avoid direct sunlight. Keep in a cool, dry place. Do not allow product to freeze.

SHELF LIFE

Shelf life approximately 8 to 12 months if stored properly.

SAFETY PRECAUTIONS

Avoid contact with eyes or prolonged contact with skin. In case of eye contact, flush with plenty of water for at least 15 minutes. Get prompt medical attention. In case of skin contact, wash thoroughly with water. Wear eye protection and non-toxic particle mask. Do not take internally. KEEP OUT OF REACH OF CHILDREN. Please refer to M.S.D.S. for additional information.

WARRANTY

PRIME is manufactured to strict quality standards using the highest quality ingredients. DARMEX fully guarantees its products and will refund or replace any product found to be defective. Liability is limited to replacement or refund only and no other warranty is expressed or implied. For individual products, DARMEX offers a 5 year material defect warranty. Please see written warranties for further details.

DARMEX is unable to accept responsibility for job conditions, workmanship, climate, damages due to transport, improper design, engineering or construction, or non performance of adjacent materials. DARMEX products are intended for use by qualified professionals and are to be applied in accordance with all manufacturers' specifications. DARMEX disclaims all, and assumes no, liability for on-site visits by any DARMEX representative. DARMEX also disclaims all warranties, expressed or implied, except written warranties issued by in accordance with DARMEX's Warranty Programs.

If further information is required, please contact your DARMEX dealer.